



TANK BOUCLE'

CAT.TF

Composizione <i>Composition</i>		78% PC + 20% PL + 2% VI	
Altezza <i>Width</i>	UNI EN 1773	140 cm (+/- 2cm)	
Peso al metro lineare <i>Weight per linear meter</i>	UNI 5114	1190 g/m (+/- 4%)	
Peso al metro quadro <i>Weight per square meter</i>	UNI 5114	850 g/m ² (+/- 4%)	
Resistenza all'abrasione <i>Abrasion Resistance</i>	ISO 12947-2	60.000 rubs	
Resistenza al Pilling <i>Pilling Resistance</i>	ISO 12945-2	4/5	
Resistenza colore allo sfregamento <i>Colour fastness to rubbing</i>	ISO 105-X12	Sfregamento a SECCO <i>Rubbing (Dry)</i> 4/5	Sfregamento a UMIDO <i>Rubbing (Wet)</i> 3/4
Resistenza del colore alla luce <i>Colour fastness to light</i>	ISO 105 B02	5/6	
Resist. allo scorrimento delle cuciture <i>Seam slippage</i>	ISO 13936-2	Ordito <i>Warp</i> 2 mm	Trama <i>Weft</i> 1 mm



NOTE | NOTES

- non centrifugare
do not centrifugate
- non utilizzare detergenti contenenti agenti ossidanti o schiarenti
do not use detergents containing oxidizing or brightening agents